



# ***Installation Instructions***

For:

## **FL License Plate Relocation Bracket**

(PN: LSM100)



1. Since this part is manufactured out of stainless steel any fine scratches incurred during the manufacturing process can be buffed out using a leading metal polish. Keep in mind that once installed no part of this bracket will be visible.
2. Begin installation by completely removing the stock taillight unit from the fender. This will allow easy access to the turn-signal light bar mounting bolts. (The bolts may also be accessed from the bottom of the fender if the bike is not lowered and a lift is available.)
3. Reaching into the fender loosen the two mounting bolts that hold the turn-signal light bar to the fender. **DO NOT REMOVE THE BOLTS.**
4. Removing one bolt at a time install the bracket... Remove one bolt, insert the bracket between the light bar and the fender, replace the bolt then do the other side the same way.
5. Tighten the mounting bolts snugly. Some minor alignment may be required during tightening.
6. Check to see that the rubber bumper at the bottom rear of the license plate bracket is touching the fender. If it is not, remove the bracket in reverse order and gently bend the bracket towards the fender. **FAILURE TO DO THIS MAY RESULT IN BREAKAGE OF THE PART AND IS NOT COVERED UNDER WARRANTY.**
7. Retighten the bolts.
8. Replace taillight.
9. Install license plate.

**Note:** Many states require direct illumination of the license plate. It is the user's responsibility to know the law in your area. Weekend Concepts is not responsible for violations of the law whatsoever.

Check your local dealer or reference the Drag Specialties Fat Book for license plate illumination options. Or go to [www.lazerstar.net](http://www.lazerstar.net).

**Warranty:** See Weekend Concepts general warranty at: [www.weekendconcepts.com](http://www.weekendconcepts.com). In addition this bracket is warranted against defects in workmanship for as long as the original buyer owns it. For more information please call 1-800-624-6234.



# ***Installation Instructions***

*For:*

## **FL License Plate Relocation Bracket**

(PN: LSM100)



1. Since this part is manufactured out of stainless steel any fine scratches incurred during the manufacturing process can be buffed out using a leading metal polish. Keep in mind that once installed no part of this bracket will be visible.
2. Begin installation by completely removing the stock taillight unit from the fender. This will allow easy access to the turn-signal light bar mounting bolts. (The bolts may also be accessed from the bottom of the fender if the bike is not lowered and a lift is available.)
3. Reaching into the fender loosen the two mounting bolts that hold the turn-signal light bar to the fender. **DO NOT REMOVE THE BOLTS.**
4. Removing one bolt at a time install the bracket... Remove one bolt, insert the bracket between the light bar and the fender, replace the bolt then do the other side the same way.
5. Tighten the mounting bolts snugly. Some minor alignment may be required during tightening.
6. Check to see that the rubber bumper at the bottom rear of the license plate bracket is touching the fender. If it is not, remove the bracket in reverse order and gently bend the bracket towards the fender. **FAILURE TO DO THIS MAY RESULT IN BREAKAGE OF THE PART AND IS NOT COVERED UNDER WARRANTY.**
7. Retighten the bolts.
8. Replace taillight.
9. Install license plate.

**Note:** Many states require direct illumination of the license plate. It is the user's responsibility to know the law in your area. Weekend Concepts is not responsible for violations of the law whatsoever.

Check your local dealer or reference the Drag Specialties Fat Book for license plate illumination options. Or go to [www.lazerstar.net](http://www.lazerstar.net).

**Warranty:** See Weekend Concepts general warranty at: [www.weekendconcepts.com](http://www.weekendconcepts.com) in addition this bracket is warranted against defects in workmanship for as long as the original buyer owns it. For more information please call 1-800-624-6234.